

TEPLORE

Tensorpack T

Air-cooled · C&I; · 400 V

Models & Specifications

Model	Rated power	Energy
Tensorpack T-B217-G100	100 kW	217 kWh
Tensorpack T-B241-G100	100 kW	241 kWh
Tensorpack T-B265-G100	100 kW	265 kWh
Tensorpack T-B434-G100	100 kW	434 kWh
Tensorpack T-B482-G100	100 kW	482 kWh
Tensorpack T-B530-G100	100 kW	530 kWh
Tensorpack T-B265-G130	130 kW	265 kWh
Tensorpack T-B434-G130	130 kW	434 kWh
Tensorpack T-B482-G130	130 kW	482 kWh
Tensorpack T-B530-G130	130 kW	530 kWh
Tensorpack T-B120-H50	50 kW	120 kWh
Tensorpack T-B217-H50	50 kW	217 kWh
Tensorpack T-B241-H50	50 kW	241 kWh
Tensorpack T-B217-H100	100 kW	217 kWh
Tensorpack T-B241-H100	100 kW	241 kWh
Tensorpack T-B265-H100	100 kW	265 kWh
Tensorpack T-B265-H125	125 kW	265 kWh

All variants share the same platform; power and energy vary by model. Full technical datasheet (dimensions, weight, certifications, grid parameters) — coming soon. For detailed specifications and quotations, contact sales@teplore.com.

